



TEST TECHNOLOGY INTERNATIONAL, INC.

Model 6800-66K

SPECIFICATIONS:

Grid Size: Bottom: Up to 14.4 x 11.2 inches
Top: Up to 14.4 x 11.2 inches

Points: 32,256 Bottom 70 mil configuration
32,256 Top 70 mil configuration

Test Voltage: 10 – 250 VDC Programmable

Test Resistance:
Isolation
10 K - 10 MOhms Standard
100 MOhms *Optional*

Continuity
10 - 1000 Ohms Standard
5 Ohms *Optional*
1 Ohm *Optional*

Test Current: Maximum of 20 mA

Control Unit: MS-DOS Compatible Computer
Windows GUI *Optional*

Ohmega Option: Testing Planar Resistors or Carbon PCB

Data Storage: HDD & 3 1/2" FDD

Test Mode: Continuity / Leakage / Ohmega

Test Environment:

Temperature: 50 - 90 °F (10 - 32 °C)

Humidity: Less than 50% non-condensing

Power Supply: 120 VAC, 60 Hz @ 5 AMPS



Printer: 40 Column Dot Matrix
Thermal Printer *Optional*

Display: LCD Flat Panel Display

Air Supply: 90 - 100 PSI (6 - 7 kPa) @ 8 CFM

Dimensions: 41 (w) x 52 (d) x 81 (h) in
1040 (w) x 1320 (d) x 2045 (h) mm

Weight: 2500 lbs. (1136 kgs) Approx.

“A Commitment to Cost Effective Test Solutions!”



Test Technology International, Inc.
1601 Fairview Drive
Carson City, NV 89701 USA
Tel: +1 (775) 885-8015
FAX: +1 (775) 885-8028
E-mail: test@ttiusa.com
Website: <http://www.ttiusa.com>